

Single-Path High-Performance Sling with K-Spec® Core Yarn

Slingmax® Single-Path Slings are the only single-path, high-performance fiber roundslings available with the Check-Fast® Inspection System and Covermax® Cover.

The Covermax® Cover is the most durable cover available for a synthetic sling. Also available in polyester with a polyester cover and polyester core yarn.



SPECIALTY SLINGS

Single-Path Extra Covermax® with Check-Fast® Inspection System

Single-Path K-Spec® Sling Stock No.	Rated Capacities (Lbs.)					Approximate Weight (Lbs. per Ft.) (Bearing-Bearing)	Nominal Body Width (Inches)*
	Vertical	Choker	Vertical Basket	Basket Hitches			
			90°	60°	45°		
SPXCF 500	5,000	4,000	10,000	8,660	7,070	.34	2.5"
SPXCF 1000	10,000	8,000	20,000	17,320	14,140	.38	2.5"
SPXCF 1500	15,000	12,000	30,000	25,980	21,210	.44	2.5"
SPXCF 2000	20,000	16,000	40,000	34,640	28,280	.52	2.5"
SPXCF 2500	25,000	20,000	50,000	43,300	35,350	.59	3"
SPXCF 3000	30,000	24,000	60,000	51,960	42,420	.65	3"
SPXCF 4000	40,000	32,000	80,000	69,280	56,560	.85	3"
SPXCF 5000	50,000	40,000	100,000	86,600	70,700	.98	4"
SPXCF 6000	60,000	48,000	120,000	103,920	84,840	1.11	4"
SPXCF 7000	70,000	56,000	140,000	121,240	98,980	1.24	4"
SPXCF 8500	85,000	68,000	170,000	147,220	120,190	1.63	5"
SPXCF 10000	100,000	80,000	200,000	173,200	141,400	1.81	5"

DO NOT EXCEED RATED CAPACITY

DO NOT EXCEED RATED CAPACITY

Single-Path Polyester with Check-Fast® Inspection System

Single-Path Polyester Roundslings Stock No.	Rated Capacities (Lbs.)					Approximate Weight (Lbs. per Ft.) (Bearing-Bearing)	Nominal Body Width (Inches)*
	Vertical	Choker	Vertical Basket	Basket Hitches			
			90°	60°	45°		
Spcf/SPF 300	3,000	2,400	6,000	5,196	4,242	.30	2.5"
Spcf/SPF 450	4,500	3,600	9,000	7,794	6,363	.45	2.5"
Spcf/SPF 600	6,000	4,800	12,000	10,392	8,484	.48	2.5"
Spcf/SPF 900	9,000	7,200	18,000	15,588	12,726	.70	2.5"
Spcf/SPF 1200	12,000	9,600	24,000	20,784	16,968	.90	3"
Spcf/SPF 1400	14,000	11,200	28,000	24,248	19,796	.95	3"
Spcf/SPF 1700	17,000	13,600	34,000	29,444	24,038	1.20	3"
Spcf/SPF 2200	22,000	17,600	44,000	38,104	31,108	1.40	3"
Spcf/SPF 2600	26,000	20,800	52,000	45,032	36,764	1.70	4"
Spcf/SPF 3200	32,000	25,600	64,000	55,424	45,248	1.90	4"
Spcf/SPF 5000	50,000	40,000	100,000	86,600	70,700	2.70	5"
Spcf/SPF 6000	60,000	48,000	120,000	103,920	84,840	3.00	5"

DO NOT EXCEED RATED CAPACITY

DO NOT EXCEED RATED CAPACITY

WARNING Sling can fail if damaged, misused or overloaded. Inspect before use. Damaged sling shall not be used. Use only if trained. Do not exceed rated capacity. Protect sling from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali and temperature over 180°F. DEATH or INJURY can occur from improper use or maintenance.